

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

1 Identification

- **Product identifier**
- **Trade name:** Divergent 880 Indoor/Outdoor Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Divergent Adhesives, LLC
176 Glenwood LN.
Gray Court, SC 29645
- **Emergency telephone number:** (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

1,2-benzisothiazol-3(2H)-one
ethyl acrylate

- **Hazard statements**

May cause an allergic skin reaction.
Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
Health = 1
Fire = 0
Reactivity = 0
- **HMIS-ratings (scale 0 - 4)**
Health = 1
Fire = 0
Reactivity = 0
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1332-58-7	Kaolin	23.0%
57-13-6	urea	1.0%
140-88-5	ethyl acrylate	0.75%
2634-33-5	1,2-benzisothiazol-3(2H)-one	0.1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	140 mg/m ³
57-13-6	urea	30 mg/m ³
140-88-5	ethyl acrylate	8.3 ppm
141-43-5	2-aminoethanol	6 ppm

- **PAC-2:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m ³
57-13-6	urea	280 mg/m ³
140-88-5	ethyl acrylate	36 ppm
141-43-5	2-aminoethanol	170 ppm

- **PAC-3:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	8,900 mg/m ³
57-13-6	urea	1,700 mg/m ³
140-88-5	ethyl acrylate	240 ppm
141-43-5	2-aminoethanol	1,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

1332-58-7 Kaolin	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction, A4
57-13-6 urea	
WEEL	Long-term value: 10 mg/m ³
140-88-5 ethyl acrylate	
PEL	Long-term value: 100 mg/m ³ , 25 ppm Skin
REL	See Pocket Guide App. A
TLV	Short-term value: 15 ppm Long-term value: 5 ppm A4

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 4)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

- **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

- **Density:** Not determined.

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

- **Solvent content:**

- **Organic solvents:** 0.6 %

- **Water:** 23.0 %

- **VOC content:** 0.58 %
5.8 g/l / 0.05 lb/gal

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

57-13-6 urea

Oral	LD50	8,471 mg/kg (rat)
------	------	-------------------

140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

140-88-5	ethyl acrylate	2B
----------	----------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 7)

· TSCA (Toxic Substances Control Act):		
1332-58-7	Kaolin	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
68131-77-1	Petroleum Hydrocarbon Resin	ACTIVE
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	ACTIVE
57-13-6	urea	ACTIVE
140-88-5	ethyl acrylate	ACTIVE
141-43-5	2-aminoethanol	ACTIVE
2634-33-5	1,2-benzisothiazol-3(2H)-one	ACTIVE

· Hazardous Air Pollutants	
140-88-5	ethyl acrylate

· **Proposition 65**

· Chemicals known to cause cancer:	
140-88-5	ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
57-13-6	urea	II

· TLV (Threshold Limit Value)		
1332-58-7	Kaolin	A4
140-88-5	ethyl acrylate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
140-88-5	ethyl acrylate

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

1,2-benzisothiazol-3(2H)-one
ethyl acrylate

· **Hazard statements**

May cause an allergic skin reaction.
Suspected of causing cancer.

· **Precautionary statements**

Obtain special instructions before use.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/14/2022

Reviewed on 11/14/2022

Trade name: Divergent 880 Indoor/Outdoor Adhesive

(Contd. of page 8)

Do not handle until all safety precautions have been read and understood.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Technical Department
- **Contact:** Technical Director
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Sensitization - Skin 1: Skin sensitisation – Category 1
 - Carcinogenicity 2: Carcinogenicity – Category 2

US