

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

1 Identification

- **Product identifier**
- **Trade name:** Wall Base Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Divergent Adhesives, LLC
176 Glenwood LN.
Gray Court, SC 29645
- **Emergency telephone number:**
CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

ethyl acrylate

1,2-benzisothiazol-3(2H)-one

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: Wall Base Adhesive

(Contd. of page 1)

If on skin: Wash with plenty of water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1332-58-7	Kaolin	34.04%
140-88-5	ethyl acrylate	2.49%
1336-21-6	ammonia	1.18%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: **Wall Base Adhesive**

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

140-88-5	ethyl acrylate	8.3 ppm
1336-21-6	ammonia	61 ppm
57-13-6	urea	30 mg/m ³
9016-45-9	nonylphenoethoxylates	43 mg/m ³

- **PAC-2:**

140-88-5	ethyl acrylate	36 ppm
1336-21-6	ammonia	330 ppm
57-13-6	urea	280 mg/m ³
9016-45-9	nonylphenoethoxylates	470 mg/m ³

- **PAC-3:**

140-88-5	ethyl acrylate	240 ppm
1336-21-6	ammonia	2,300 ppm
57-13-6	urea	1,700 mg/m ³
9016-45-9	nonylphenoethoxylates	5,400 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: **Wall Base Adhesive**

(Contd. of page 3)

- Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 2* mg/m³
E; as respirable fraction

140-88-5 ethyl acrylate

PEL Long-term value: 100 mg/m³, 25 ppm
Skin

REL See Pocket Guide App. A

TLV Short-term value: 61 mg/m³, 15 ppm
Long-term value: 20 mg/m³, 5 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: **Wall Base Adhesive**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

100 °C (212 °F)

- **Flash point:**

Not applicable.

- **Flammability (solid, gaseous):**

Not applicable.

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:**

Not determined.

- **Upper:**

Not determined.

- **Vapor pressure at 20 °C (68 °F):**

23 hPa (17.3 mm Hg)

- **Density:**

Not determined.

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: Wall Base Adhesive

(Contd. of page 5)

- | | |
|----------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Water: | 21.2 % |
| VOC content: | 0.00 % |
| | 0.0 g/l / 0.00 lb/gal |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	32,129 mg/kg (rat)
Dermal	LD50	73,655 mg/kg (rabbit)
Inhalative	LC50/4 h	87,550 mg/l (rat)

140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

140-88-5 ethyl acrylate

2B

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: Wall Base Adhesive

(Contd. of page 6)

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|-----------------|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADN, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, ADN, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADN, IMDG, IATA · Class | not regulated |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · Environmental hazards: | Not applicable. |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: **Wall Base Adhesive**

(Contd. of page 7)

- | | |
|--|-----------------|
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**

- TSCA (Toxic Substances Control Act):**

1332-58-7	Kaolin
140-88-5	ethyl acrylate
1336-21-6	ammonia
57-13-6	urea
9016-45-9	nonylphenoethoxylates
2634-33-5	1,2-benzisothiazol-3(2H)-one
7732-18-5	water, distilled, conductivity or of similar purity

- Proposition 65**

- Chemicals known to cause cancer:**

140-88-5	ethyl acrylate
----------	----------------

- Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- Carcinogenic categories**

- EPA (Environmental Protection Agency)**

57-13-6	urea		II
---------	------	--	----

- TLV (Threshold Limit Value established by ACGIH)**

1332-58-7	Kaolin		A4
140-88-5	ethyl acrylate		A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5	ethyl acrylate
----------	----------------

- GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms**



GHS07 GHS08

- Signal word** Warning

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2019

Reviewed on 02/08/2019

Trade name: Wall Base Adhesive

(Contd. of page 8)

- **Hazard-determining components of labeling:**

ethyl acrylate
1,2-benzisothiazol-3(2H)-one

- **Hazard statements**

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Technical Department

- **Contact:** Technical Director

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2