



F9100 CARPET PAD CEMENT

Divergent F9100 Carpet Pad Adhesive is an Extremely Flammable solvent-based pad adhesive that is recommended for permanently fastening carpet padding over any approved flooring surface. F9100 has strong initial tack and high strength, which prevents movement of padding during stretching or life of the carpet. NOTE: Due to continuing development of new and different types of backings, padding and methods of application, we recommend that any unfamiliar materials be thoroughly tested before attempting a complete installation.

Packaging: 1 gallon F-style can



FOR PROFESSIONAL USE ONLY!



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com

©2022 Divergent Adhesives, LLC.



F9100 CARPET PAD CEMENT

FOR PROFESSIONAL USE ONLY!

APPROVED SUBSTRATES

- › Concrete
- › Fiber Cement Underlayment
- › Properly prepared VCT (single layer)
- › APA Approved Plywood
- › Portland Based Patching Underlayments
- › Properly prepared sheet vinyl (single layer)
- › Terrazzo
- › Radiant Heated Sub-floors

DIRECTIONS

1. The floor must be clean, dry, and free of dust, dirt and grease or oil.
2. There is an inner seal under the screw cap on the container that should be pierced or removed. Punch a 1/8" diameter hole in this seal.
3. Pour adhesive on the floor in a 3" or 4" bead from the wall. Use a zigzag pattern at the padding seam.
4. Let the adhesive dry two to five minutes.
5. Drop padding into exact position desired and apply pressure by walking over the adhesive area.
6. Install carpet immediately after laying padding. Padding will not slip once placed into adhesive.
7. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

CLEAN UP

Mineral Spirits can be used to clean up excess adhesive or spills.

PHYSICAL PROPERTIES

Open Time up to 2 hours · Shelf Life One Year in unopened container · Color Yellow Brown

WARRANTY

Divergent Adhesives offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 877-GLU-DUDE or visiting DivergentAdhesives.com.



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com

©2022 Divergent Adhesives, LLC.