

FAST TACK ADHESIVE

Divergent Fast Tack Adhesive was developed to offer the user a product that is versatile to use on a wide range of substrates. Approved substrates include wood, foam, fabric, nonwovens, paper, drywall, masonry, plastic and painted surfaces. RESTRICTIONS: NOT FOR USE WITH VINYL PRODUCTS. Materials to be bonded must be clean, dry and free of oil, dirt, moisture, grease, etc.

Packaging: 12 oz can

FOR PROFESSIONAL USE ONLY!

DIVERGENT ADHESIVES

DIVERGENT FAST TACK ADHESIVE

Instant Tack
Flexible Bond Line
Clear
Low Soak In

ANGER:

EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. EVE IRRITANT. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. Read Cautions on Side Panel. WET WT. 12 OZ (340 g)



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com ©2022 Divergent Adhesives, LLC.



FAST TACK ADHESIVE

FOR PROFESSIONAL USE ONLY!

NOT RECOMMENDED FOR USE WITH ANY VINYL PRODUCTS, CANNOT BE USED WITH REDUCERS, STAIR NOSINGS OR TRANSITIONS THAT CONTAIN PVC.

SURFACE PREPARATION

Materials to be bonded must be clean and dry, free of oil, dirt, paint, moisture, grease, etc.

DIRECTIONS

- 1. Spray in area equipped to exhaust the solvent vapor, introduce as much fresh air as possible during use.
- 2. Both surfaces should be clean and smooth.
- 3. Coat both surfaces to be bonded with a pattern uniform in appearance. The provided tip will allow control of the lace spray pattern.
- 4. On porous surfaces, spray both materials and allow to dry to the touch, typically this takes 1-2 minutes. Do not allow more than 5 minutes to bond the material.
- 5. On non-porous materials spray both surfaces and allow one minute before bonding.
- 6. Apply lightly to one side of the material for a non-permanent bond.
- 7. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

READ SAFETY DATA SHEET FOR ADDITIONAL INFORMATION

SHELF LIFE

One year shelf life.

WARRANTY

Divergent Adhesives offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 877-GLU-DUDE or visiting Divergentadhesives.com.



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com