Printing Date 05/21/2020

Revision Number 1

Revision Date 05/21/2020

# 1 Identification

#### · Product identifier

- Trade name: <u>TimberTight AF</u>
- *Relevant identified uses of the substance or mixture. Industrial Use Only. Adhesive*
- · Application of the substance / the mixture Adhesive
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Divergent Adhesives LLC
  176 Glenwood Lane Gray Court South Carolina
  29645 Phone 1-877-458-3833 Sonny@divergentadhesives.com
- · Information department: Global Regulatory Department.
- · Emergency telephone number:
- Emergency Telephone Number: CANUTEC Collect: (613) 996-6666 (24-hour hotline)

#### **2** *Hazard*(*s*) *identification*

· Classification of the substance or mixture

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B H340 May cause genetic defects.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



Printing Date 05/21/2020

Revision Number 1

Revision Date 05/21/2020

## Trade name: TimberTight AF

	(Contd. of page 1)
Signal word Danger	
· Hazard statements	
Harmful if inhaled.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction.	
May cause genetic defects.	
May cause respiratory irritation.	
May cause damage to organs through prolonged or repeated exposure.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	
If on skin: Wash with plenty of water.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen	t and easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
If experiencing respiratory symptoms: Call a poison center/doctor.	
Wash contaminated clothing before reuse.	
Store in a well-ventilated place. Keep container tightly closed.	
Store locked up.	1.1
Dispose of contents/container in accordance with local/regional/national/international regional/	ulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = $0$	
$\frac{2}{Reactivity} = 0$	
HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{2} Health = *2$	
FIRE 0 $Fire = 0$	
<b>PHYSICAL HAZARD</b> Physical Hazard = $0$	
Other hazards	
Results of PBT and vPvB assessment	
<b>PBT:</b> Not applicable.	

• *PBT:* Not applicable. • *vPvB:* Not applicable.

(Contd. on page 3)

USA

Printing Date 05/21/2020

**Revision Number 1** 

Revision Date 05/21/2020

Trade name: TimberTight AF

(Contd. of page 2)

2.5-10%

2.5-10%

#### **3** Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture

#### • Hazardous components:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues{polymer exempt} 2.5-10%

#### **4** First-aid measures

· Description of first aid measures

#### • After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **5** Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray.
- Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

#### 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- $\cdot$  Methods and material for containment and cleaning up:
- Use neutralizing agent. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections

Neutralization solutions:

- 1. A mixture of 90% water. 3-8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.
- 2. A mixture of 80% water, 20% non-ionic surfactant.

Apply solution. Wait 15 minutes. Collect in open-head container. Re-apply until surface is decontaminated. Apply (Contd. on page 4)

USA

Printing Date 05/21/2020

Revision Number 1

Revision Date 05/21/2020

#### Trade name: TimberTight AF

(Contd. of page 3) drum lid but DO NOT secure. Let containers vent for 72 hours allowing carbon dioxide to escape. Secure drum lid.

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Open and handle receptacle with care. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about protection against explosions and fires: Product reacts with water. Reaction may produce heat and/or gases.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Protect from moisture. Keep packages dry.
- · Information about storage in one common storage facility:
- Store away from oxidizing agents. Keep away from open flames and high temperatures.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Protect from humidity and water.
- Protect from contamination.
- Store under dry inert gas.
- Store in dry conditions.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

- PEL Ceiling limit value: 0.2 mg/m<sup>3</sup>, 0.02 ppm
- REL Long-term value: 0.05 mg/m<sup>3</sup>, 0.005 ppm Ceiling limit value: 0.2\* mg/m<sup>3</sup>, 0.02\* ppm \*10-min
- TLV Long-term value: 0.051 mg/m<sup>3</sup>, 0.005 ppm

#### • Additional information:

MDI products have poor warning properties, since recognition of an odor is far above the TLV. Observe OSHA regulations for respirator use (29 CFR 1910.134).

The lists that were valid during the creation were used as basis.

(Contd. on page 5)

USA -

Printing Date 05/21/2020

**Revision Number 1** 

Revision Date 05/21/2020

Trade name: TimberTight AF

(Contd. of page 4)

USA

- · Exposure controls
- · Personal protective equipment (see listings below)

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR Chloroprene rubber, CR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

• **Body protection:** Apron

Protective work clothing

<ul> <li>Information on basic physic</li> <li>General Information</li> </ul>	al and chemical properties	
· Appearance:	Durate	
Form: Color:	Paste Greenish	
· Odor:	Sweetish	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point:	Undetermined.	
<b>Boiling point:</b>	Undetermined	
· Flash point:	Not applicable.	

Revision Date 05/21/2020

Printing Date 05/21/2020

Revision Number 1

Trade name: TimberTight AF

	(Ce	ontd. of page
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Flammable limits:		
Lower:	Not determined	
Upper:	Not determined	
Vapor pressure:	Not determined.	
Specific gravity:	1.27	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	Not available	
Solids content:	Not available.	
Other information	VOC content: <100 g/l	

## **10 Stability and reactivity**

\*

• Chemical stability • Thermal decomposition / conditions to be avoided: Moisture	
· Possibility of hazardous reactions	
Contact with moisture, other materials that react with isocyanates, or temperatures al polymerization.	bove 350F, may cause
• Conditions to avoid Avoid high temperatures. Avoid freezing.	
· Incompatible materials:	
Reacts with amines.	
Reacts with alcohols.	
Reacts with alkali (lyes).	
Reacts with water.	
Copper and copper alloys.	
· Hazardous decomposition products:	
Carbon monoxide	
Carbon dioxide	
Nitrogen oxides	
Isocyanate	
Isocyanic acid	
Possible in traces.	
	(Contd. on

(Contd. on page 7) USA

Printing Date 05/21/2020

Revision Number 1

Revision Date 05/21/2020

Trade name: TimberTight AF

Hydrogen cyanide (prussic acid)

#### **11** Toxicological information

· Information on toxicological effects

· Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

*Oral LD50* >5,000 mg/kg (rat)

*Dermal LD50* >3,000 *mg/kg* (*rab*)

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

#### · Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

 $\cdot$  on the eye:

Causes serious eye irritation.

Vapors may be irritating to the eyes.

#### • Sensitization:

Inhalation - Sensitization possible through inhalation.

Skin Contact - Sensitization possible through skin contact.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues (polymer exempt)

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12** Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

3

3

(Contd. of page 6)

**Revision Number 1** 

Revision Date 05/21/2020

Trade name: TimberTight AF

· Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

· Waste treatment methods

· Recommendation: Comply with current regulations.

· Uncleaned packagings:

· Recommendation: Comply with current regulations.

## **14 Transport information**

#### **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues {polymer exempt}

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Hazardous Air Pollutants

101-68-8 4,4'-methylenediphenyl diisocyanate

• Proposition 65 Please contact supplier of this product regarding Proposition 65 information.

(Contd. on page 9)

(Contd. of page 7)

USA

Printing Date 05/21/2020

**Revision Number 1** 

Revision Date 05/21/2020

#### Trade name: TimberTight AF

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

#### · Cancerogenity categories

· EPA (Environmental Protection Agency)

101-68-84,4'-methylenediphenyl diisocyanate9016-87-9diphenylmethanediisocyanate,isomeres and homologues{polymer exempt}

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

#### · MAK (German Maximum Workplace Concentration)

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues (polymer exempt)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

#### · National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. *Exceptions can be made by the authorities in certain cases.* 

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, the supplier/manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will the supplier/ manufacturer be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· Department issuing SDS: Global Regulatory Department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

- DOT: US Department of Transportation
- IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

- HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- *PBT: Persistent, Bioaccumulative and Toxic*

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. of page 8)

D, CBD

4

4

CBD

<sup>·</sup> Creation Date: 05/21/2020

<sup>·</sup> Date of preparation / last revision 05/21/2020 / -

<sup>•</sup> Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

Printing Date 05/21/2020

Revision Number 1

Revision Date 05/21/2020

#### Trade name: TimberTight AF

REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Muta. 1B: Germ cell mutagenicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 (Contd. of page 9)

US/