



4547 BULLETPROOF ADHESIVE

Divergent 4547 Bulletproof Adhesive is a premium-grade formula designed for interior/exterior construction, installation and repair projects. Approved for common building materials including wood, metal, brick, marble, ceramic tile, concrete, drywall, plywood, OSB, particleboard and wet, frozen and treated lumber.

Packaging: 28 oz cartridges



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com

©2025 Divergent Adhesives, LLC.



4547 BULLETPROOF ADHESIVE

DIRECTIONS

1. Surfaces must be clean and free of any material that may prevent adequate adhesion.
2. Cut tip on slant for 1/4" to 3/8" bead. For subfloors, cut tip straight across. Puncture inner seal and place in cartridge gun.
3. Apply adhesive to one of the surfaces in either continuous or spot bead.
4. Adhere materials within 15 minutes. Press material firmly together using a slight twisting motion. Certain large applications may require additional bracing until adhesive has dried. Note: For subfloors, apply adhesive to joists for one sheet at a time. Nail or crew each sheet as recommended by the American Plywood Association.

CLEAN UP

Tools and adhesive may be cleaned with acetone or mineral spirits. Follow solvent vendor's precautions

RESTRICTIONS

4547 is not designed for continuous submersion, use on plastics, polystyrene or polyethylene foams. Do not bond one nonporous material to another since this will slow or prevent drying.

COVERAGE

Provides 85 linear feet of 1/4" bead.

CALCULATED VOC

<50 g/L.

SPECIFICATIONS

Exceeds APA AFG-01, ASTM D3498 and ASTM C557.

APPLICATION TEMP

0-100°F.

DANGER

Highly flammable liquid and vapor. Causes serious eye irritation. Suspected of causing cancer if inhaled. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed.

Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink, or smoke when using this product. Avoid contact with skin and clothing. Prolonged or repeated contact may dry skin and cause irritation. Wash hands thoroughly after handling.

FIRST AID

IF EXPOSED OR CONCERNED: Get medical attention. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. **IF ON SKIN:** Wash with plenty of soap and water. **IF SKIN IRRITATION OCCURS:** Get medical advice or attention. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove any contact lenses and continue rinsing. **IF EYE IRRITATION PERSISTS:** Get medical attention. Store in a cool, well-ventilated place. **FIRE:** Use water spray (fog), dry chemical, or CO2. Cool containers with water spray. In case of major fire and large quantities, evacuate area. Fight fire remotely due to risk of explosion. Dispose contents and container in accordance with local, regional, national, and international regulations. For additional information, refer to SDS.

WARRANTY

Divergent Adhesives LLC offers a limited liability warranty for this material when used in accordance with the label and TDS.



OUR EXPERIENCE ENSURES YOUR SUCCESS

1-877-458-3833 · 1-877-GLU-DUDE · sonny@divergentadhesives.com · divergentadhesives.com

©2025 Divergent Adhesives, LLC.